


Combe Fill South Superfund Site:

Forty Years to The Finish



Vecteezy.com



January 13, 2021

Combe Fill South Project Team

- Pamela J. Baxter, PhD, CHMM; Remedial Project Manager (US EPA)
- Bradley Williams, PhD; EPA Contract Manager (HDR)
- Patricia Parvis, PG, LSRP; Senior Project Manager (HDR)
- Andrew Watson, PE; Lead Design Engineer (HDR)
- Andrew Wadden, LSRP; RI and Pre-Design Investigation Lead (HDR)

Acknowledgments



Presentation





01 Site History

02 Regulatory History

03 Impacts of Evolving Investigative Technologies

04 Treatment of Emerging Contaminants





01


Site History












Service Layer Credits. Copyright © 2013 National Geographic Society, I-cubed
 Coordinate System: NAD 1983 StatePlane New Jersey FIPS 2900 Feet
 Projection: Transverse Mercator
 Datum: North American 1983
 Units: Foot US




- Legend**
- OU1 - Landfill Property Boundary
 - OU2 - Investigation Area




Location






Bedrock Geology







1957




1963



1970



1971



1972




1979



1987

1931

Rural Chester and
Washington Townships
Agriculture Predominates




- Opens in the 1940s
- Household wastes
- Sewage sludge
- Septic wastes

1957



- Industrial wastes
- Chemicals
- Waste Oil

1963



1970

- Soil removed down to bedrock and stockpiled
- 400 ft. long x 20 ft. wide x 20 ft. deep open trenches
- Refuse is placed on fractured rock
- Leachate, runoff enter near vertical fractures



Filiberto Landfill

1971



Filiberto to Chester Hills Landfill


First year of
regulatory
oversight

1972

Expansion begins
to the southwest
encroaching on
forested wetlands
to the west

NJ Fisheries observes
landfill "Juices"
moving to stream

NJDEP
approves trench
method of waste
disposal



Chester Hills
Landfill to
Combe Fill Corp.

1979


Shop with
Tanks

Leachate
Discharges
to Stream

Leachate
Collection
Sump


Leachate
Seeps

Discolored
Trout Stream



Discovery

- 1972 - NJDEP issued Certificate to Operate for non-hazardous and municipal solid waste
- 1973 – Fish kills in Trout Brook reported by Division of Fish and Game
- 1973 – First leachate collection and recycling system installed
- 1974 – NJDEP requests installation of monitoring wells
- 1977 – Additional monitoring wells installed
- 1978 – Change in ownership from Chester Hills to Combe Fill Corp.
- 1979 – Runoff from exposed waste observed entering bedrock fractures
- 1981 – Combe Fill Corp. reports acceptance of pharmaceutical waste and fiber drums previously containing organic chemicals



1979 Inspection


FILIBERTO LANDFILL AREA AND ENVIRONS



FRESH WATER Pond
Polluted Ponds or Leachate Ponds

FRESH WATER Stream
LANDFILL and or septic seepage from ponds or in swamp.
Polluted stream
House
well

HIGH AND DRY above headwaters of Trout Brook



100169


APPROX. SCALE 1:12,000

Discovery

- Jan 1981 – Combe Fill starts clearing forested wetlands to west for additional 100 acres
- March 1981 – Chester and Washington Townships file suit to stop landfilling, judge issues order
- April 1981 – Upper Raritan Watershed Association samples monitoring wells and surface water
- June 1981 – Residents form HALT – Help Stop a Landfill Tragedy - sample 90 wells
- Sept. 1981 – NJDEP issues order to stop landfilling due to groundwater contamination
- 1982 – Reclamation activities cease
- 1983 – Investigations commence



Site Conditions at Start of Investigations



Denville, N.J. 07834

March 12, 1986

Denville, N.J. 07834

Skelly

President Ronald Reagan
White House
1600 Pennsylvania Avenue N.W.
Washington, D.C. 20500

To The Gipper at
the White House

Frisco Hubbard
RECEIVED
4/7/86
due 4/10/86

Dear President Reagan:

Approximately five years ago I bought a home in Washington Township, Morris County, New Jersey. The home is supplied by an individual well which is used by me, my wife, and my children.

The home is within a short distance of an abandoned toxic waste site known as Combe Fill South Land Fill. The land fill was closed by order of the State Department of Environmental Protection (hereinafter referred to as D.E.P.) and is listed on the federal toxic waste super fund list for clean up at some time in the future.

We were recently notified in writing by the D.E.P. and the municipality that our drinking water could be polluted by this land fill and it was recommended that we not drink the water. I have been told by representatives of Washington Township and adjoining Chester Township that the State D.E.P. agreed to supply an alternate source of drinking water to be piped into my home at 11 East Gate Road, Long Valley, New Jersey, along with other homes surrounding the land fill, from a central water source. The D.E.P. has promised this alternate water source by the end of this year.

The purpose of this letter is to request that you and your office do whatever can be done to expedite the installation of this alternate water source.

This request is made on my behalf and on behalf of my wife and my children as well as other affected home owners. We are presently drinking bottled water but are using the well water to shower and to bathe, and I am concerned for my safety and the safety of my family and others. I understand that it will take some time to properly close the land fill, but I hope that work can begin immediately on the alternate water source.



1987

Waiting on remedial design

1995



Landfill cap under
construction 1995-1996

2006

I thought we were finished?
What's going on to the north?




2007



Landfill cap extension completed

1980s Shallow Well Data



1980s Shallow Well Data

TABLE 4-11 (Page 1 of 3)

SUMMARY OF SHALLOW MONITORING WELLS PRIORITY POLLUTANTS

Combe Fill South Landfill

PARAMETER	S-1	S-2	S-3	S-4	S-5	S-6
DATE SAMPLED	9/4/85	9/5/85	8/29/85	9/4/85	8/28/85	8/28/85
VOLATILES, ppb						
Benzene	64.7	BM @ 4.4	80.2	BM @ 4.4	ND	BM @ 4.4
Chlorobenzene	ND	30.3	21.1	18.2	ND	ND
Chloroethane	ND	ND	BM @ 10	62.0	ND	ND
Chloroform	ND	ND	ND	ND	57.5	ND
1,1-Dichloroethane	65.2	ND	51.4	BM @ 4.7	ND	ND
1,2-Dichloroethane	ND	ND	ND	6.10	ND	ND
1,1-Dichloroethylene	ND	ND	ND	ND	ND	ND
1,2-Dichloropropane	ND	ND	BM @ 6	ND	ND	ND
Ethylbenzene	ND	ND	BM @ 7.2	ND	ND	ND
Methylene chloride ^a	56.0	4.44	18.4	8.2	4.67	4.67
Tetrachloroethylene	ND	ND	BM @ 4.1	ND	ND	ND
Toluene	1370	ND	68.2	ND	ND	ND
Trans-1,2-dichloroethylene	ND	ND	8.02	ND	ND	ND
Trichloroethylene	ND	ND	4.04	ND	ND	ND
Vinyl chloride	ND	ND	BM @ 10	ND	ND	ND
ACID/PHENOLICS, ppb						
2,4-Dimethylphenol	ND	ND	ND	ND	ND	ND
2-Nitrophenol	ND	ND	ND	ND	ND	ND
Phenol	ND	ND	ND	BM @ 1.5	ND	ND


- Limited Priority Pollutant List
- High Detection Limits
- Different Contaminants of Concern

ND = Not detected.

BM = Below method detection limit.

1983-1985 RI/FS, LMS Engineers
on behalf of NJDEP

1980s Deep Well Data




LEGEND

----- COMBE FILL
----- SOUTH LANDFILL
----- PROPERTY BOUNDARY

CONCENTRATIONS OF
PRIORITY POLLUTANTS
VOC - ppb
ACID/PHENOLICS - ppb
BASE/NEUTRALS - ppb
METALS - ppm

▲ DEEP, D-SERIES WELLS

● EXISTING MONITORING WELLS



1980s Deep Well Data

TABLE 4-12 (Page 1 of 2)
 SUMMARY OF PRIORITY POLLUTANTS
 DEEP MONITORING WELLS
 Combe Fill South Landfill

PARAMETER	D-1	D-2	D-3	D-4	D-5	D-6	D-7	D-8	D-9	DW-2	DW-4
DATE SAMPLED	8/28/85	8/28/85	9/4/85	8/28/85	8/28/85	8/29/85	9/4/85	9/4/85	9/4/85	9/5/85	9/5/85
VOLATILES, ppb											
Benzene	ND	ND	ND	ND	16.9	39.1	66.4	31.5	18.6	ND	252
Chlorobenzene	ND	ND	ND	ND	ND	BM @ 6	9.88	10.8	ND	ND	BM @ 6
Chloroethane	ND	ND	ND	ND	ND	ND	22.5	74.3	BM @ 10	ND	ND
Chloroform	ND	209	ND	82.6	ND	ND	ND	ND	ND	ND	155
1,1-Dichloroethane	ND	6.41	ND	ND	10.6	BM @ 4.7	ND	14.8	30.2	ND	ND
1,2-Dichloroethane	ND	7.98	ND	ND	40.5	37.2	ND	11.2	4.54	ND	14.2
1,1-Dichloroethylene	ND	6.41	ND	ND	ND	ND	ND	ND	ND	ND	ND
1,2-Dichloropropane	ND	ND	ND	ND	ND	ND	ND	BM @ 6	ND	ND	ND
Ethylbenzene	ND	ND	ND	ND	ND	ND	34.2	11.7	ND	ND	ND
Methylene chloride ^a	5.92	176.07	16.0	ND	9.77	ND	20.0	18.8	12.6	9.3	20.6
Tetrachloroethylene	ND	14.3	ND	ND	6.89	BM @ 4.1	ND	ND	ND	ND	5.58
Toluene	ND	ND	ND	ND	ND	ND	1140	ND	ND	ND	ND
Trans-1,2-dichloroethylene	ND	ND	ND	5.40	25.8	47.5	ND	ND	ND	ND	17.5
Trichloroethylene	ND	8.34	ND	ND	2.72	26.0	ND	ND	ND	ND	56.8
Vinyl chloride	ND	ND	ND	ND	ND	BM @ 10	ND	ND	ND	ND	BM @ 10
ACID/PHENOLICS, ppb											
2,4-Dimethylphenol	ND	ND	ND	ND	ND	ND	ND	3.12	ND	ND	ND
2-Nitrophenol	ND	ND	ND	ND	ND	ND	ND	BM @ 3.7	ND	ND	ND
Phenol	ND	2.35	ND	ND	2.75	ND	ND	ND	ND	ND	ND
BASE/NEUTRALS, ppb											
Bis (2-chloroethyl) ether	ND	ND	ND	ND	ND	ND	ND	BM @ 5.9	ND	ND	ND
Bis (2-ethylhexyl) phthalate	BM @ 11	ND	ND	BM @ 10	ND	BM @ 11	ND	BM @ 10	BM @ 10	ND	ND
1,2-Dichlorobenzene	ND	ND	ND	ND	ND	ND	ND	5.58	1.92	ND	ND
1,4-Dichlorobenzene	ND	BM @ 4.6	ND	ND	BM @ 4.5	ND	ND	14.2	ND	ND	ND
Di-ethyl phthalate	ND	ND	ND	ND	BM @ 10	ND	ND	BM @ 10	ND	ND	ND
Di-n-butyl phthalate	BM @ 11	ND	ND	BM @ 10	BM @ 10	ND	ND	BM @ 10	BM @ 10	ND	BM @ 10
Di-n-octyl phthalate	BM @ 11	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Isophorone	ND	21.9	ND	ND	ND	ND	ND	ND	ND	ND	ND
Naphthalene	ND	ND	ND	ND	ND	ND	ND	3.24	ND	ND	ND
N-nitrosodiphenylamine	ND	ND	ND	ND	ND	ND	ND	BM @ 2	ND	ND	ND


- Limited Priority Pollutant List

- High Detection Limits

- Different COCs


^aCorrected based on analysis of QA/QC samples.
 ND = Not detected.

1993 to 1995 Lions and Tigers and Buried Drums, Oh My!



- 150, 55-gallon drums discovered during cap construction
- Logs show drums found as early as 1988

1993 to 1995 Lions and Tigers and Buried Drums, Oh My!




- Drum of "Aqua Velva" is a prelude of things to come




MAP LOCATION OF THE MILLSTONE CROSSING DEVELOPMENT AND EASTERN PART OF THE COMBES SOUTH LANDFILL SHOWING DOMESTIC WELL LOCATIONS, ORIENTATIONS OF GNEISSIC FOLIATION INTERPRETED FROM OPTICAL TELEVIEWER DATA, PROFILE LINE A-A', AND GEOREFERENCED BASE MAPS, PARKER RD., CHESTER TWP., MORRIS COUNTY, NEW JERSEY, N.J. GEOLOGICAL SURVEY, G.C. HERMAN, 2004 DECEMBER 29

Other's Bad Ideas – 2004 Millstone Crossing





STRUCTURAL SUMMARY OF FOLIATIONS LAYERS, FRACTURE PLANES, AND INTERSECTIONS OF STRIKE MAXIMUMS



CYCLOGRAPHIC PLOT OF 357 FRACTURES, 70 LAYERS, AND DENSITY CONTOURS OF PLANE MAXIMUMS FOR FIVE WELLS LOWER HEMISPHERE EQUAL ANGLE STROEGRPHIC PROJECTION

LEGEND:

22.13 Well ID and VO concentration (ppb)
(82) ⊕
(U) - undetected




NOTES:

- 1) BASE MAP FOR MILLSTONE CROSSING ADAPTED FROM: FINAL PLAN OF MILLSTONE CROSSING, JAN. 9, 2002, PREPARED BY ASSOCIATED CONSULTANTS, 530 EAST MAIN ST., CHESTER, N.J. 07930-0383, SCALE 1"=100'
- 2) BASE MAP FOR COMBES SOUTH LANDFILL ADAPTED FROM: SHALLOW GROUND WATER ELEVATION CONTOUR MAP, SEPTEMBER 2001, BY O'BRIEN AND GERE ENGINEERS, INC., 1/1802, SCALE 1"=300'

- Residential Developer Installed Potable Wells to 750 ft. bgs NE of Landfill
- Uncased, Open Boreholes Created New Vertical Conduits

MAP LOCATION OF THE MILLSTONE CROSSING DEVELOPMENT AND EASTERN PART OF THE COMBES SOUTH LANDFILL SHOWING DOMESTIC WELL LOCATIONS, ORIENTATIONS OF GNEISSIC FOLIATION INTERPRETED FROM OPTICAL TELEVIEWER DATA, PROFILE LINE A-A', GEOREFERENCED BASE, WELLFIELD GRID, AND STRUCTURAL LINEATIONS, PARKER RD., CHESTER TWP., MORRIS COUNTY, NEW JERSEY, N.J. GEOLOGICAL SURVEY, G.C. HERMAN, 2004 DECEMBER 29


Other's Bad Ideas – 2004 Millstone Crossing



TOPOGRAPHIC BASE MAP FROM THE U.S. GEOLOGICAL SURVEY CHESTER 7-1/2' QUADRANGLE

SCALE 1:4800

LEGEND:



NOTES:

- 1) BASE MAP FOR MILLSTONE CROSSING ADAPTED FROM: FINAL PLAN OF MILLSTONE CROSSING, JAN. 9, 2002, PREPARED BY ASSOCIATED CONSULTANTS, 530 EAST MAIN ST., CHESTER, N.J. 07930-0383, SCALE 1"=100'
- 2) BASE MAP FOR COMBES SOUTH LANDFILL ADAPTED FROM: SHALLOW GROUND WATER ELEVATION CONTOUR MAP, SEPTEMBER 2001, BY O'BRIEN AND GERE ENGINEERS, INC., 1/18/02, SCALE 1"=300'
- 3) WELLFIELD GRID GENERATED WITH 100' CELLS



Statistical maximum trend and plunge of planar intersections of foliation layering (S0), and brittle extension (S1) and shear (S2) fractures. Marker with 7 degree plunge occurs with 16% contour interval and the rest are the others are 8 percent

- 2004 NJGS hydrogeological interpretation
- Optical televiewer
- Fluid-temperature
- Fluid electrical-conductivity
- Heat-pulse flow meter geophysical logs
- Five of the 15, 6-inch diameter domestic wells developed in Middle Proterozoic gneissic bedrock



Discovery of North Waste Cell

- Discovered by NJDEP in 2001 during soil gas probe installation
- Test pit investigation 2003 to 2004
- Remediation 2006 to 2007





Discovery of North Waste Cell



- Not apparent from site history – no documentation
- Not obvious on aerial photographs
- Very close to previous buried drum discoveries
- August 1966 New York Times found buried within



Discovery of North Waste Cell



- Start of Remedial Action June 2006
- Excavation, Characterization, Off-Site Disposal
- 27,327 Tons Non-Hazardous Soil and Debris
- Backfill (left, foreground)
- Extension of Cap over Excavated Area in 2007


Treasures of the North Waste Cell

- “Warehouses” of off-spec personal care products – first appearance of the *primary contaminant of concern*
- Baby Magic Baby Lotion
 - 15 deaths in US
 - > 1% Hexachlorophene banned 1972
- Mennen shaving cream
- Over-the-counter medications
 - Pills
 - Liquids
 - Aerosols



Treasures of the North Waste Cell

- Poison (Cyanide)
 - Not a contaminant of concern
- Chloroflourocarbons
 - Were COCs at the start of 2011 RI
 - Not COCs at the time of the 2018 ROD
- Simple PRP identification
 - Names and addresses of PRPs on labels
 - Majority of PRPs were Morris County, New Jersey pharmaceutical companies



Treasures of the North Waste Cell



- Pharmaceutical constituents
 - Barbiturates (some experimental)
 - Phenobarbital on product labels
 - Phenobarbital in potable wells
 - Butylbarbital
 - Animal tranquilizers
- Backhoe buckets of pills
 - Who knows what was in those?



Treasures of the North Waste Cell

- Experimental Chemical #993
- Hydrocyanic Acid
- North Waste Cell Conclusion:
 - Likely primary source of **1,4-Dioxane** from personal care products and pharmaceuticals; not present as a solvent stabilizer
 - Source of phenobarbital
 - Source of chlorofluorocarbons
 - Variety of pharmaceuticals – what does the future hold for these potential COCs currently without standards and lacking carcinogenicity data?





02

Regulatory History

OU1 Remediation Timeline

- 1983 - Listed on NPL
 - Hazardous Ranking score $49 \geq 28$
- 1984 - 1985 - RI/FS performed by NJDEP
- 1986 - OU1 Record of Decision
- 1993 - Submittal of final Design Report
- January 1993 - Commencement of construction
- September 1997 - Completion of construction
Conducted 1-year operation and functional period
 - Construction cost approx. \$26 M
- July 30, 2009 - EPA took over RI/FS OU2 activities from NJDEP
- June 30, 2011 - NJDEP issued a detailed closeout report of OU1.



Aerial view of treatment plant under construction – August 25, 1994 NJDEP Closeout Report 6/2011

Original OU1 – 1986 ROD

- Alternate water supply
- Landfill capping
- Landfill gas collection
- Pump and treat, discharge to Trout Brook
- Stormwater management
- Site Security
- Periodic monitoring
- Supplemental FS for deep aquifer
- April 17, 2006 ESD
 - Revision to the passive landfill gas system



**Aerial view of landfill looking west during construction –
May 30, 1995 NJDEP Closeout Report 6/2011**

- Estimated capital cost - \$46,060,700, and estimated O&M cost - \$673,000 for first five years.

Enforcement

Cost Recovery –

- In 1985, EPA filed an application in bankruptcy court seeking reimbursement of Superfund monies spent at the Site to date.
 - Since limited funds remained in the bankruptcy estate, EPA and CFC reached a settlement in which CFC paid \$50,000 in May 1986 to resolve EPA's Superfund claims.
- 2005 - Initial settlement resulted with former owner/operators paid NJDEP and EPA \$12,500,000 in costs




Enforcement

Cost Recovery –

- 2009 - Second settlement
 - 300 private parties and municipalities
 - EPA paid \$69 million in past costs
 - \$3.2 M paid to the state for natural resource damages
 - NJDEP paid \$27 million annuity to fund O&M and future work



2011 Potable Well Sampling




1,4 Dioxane Treatability Study for Private Wells

- EPA, via Environmental Restoration, LLC (ER), conducted a treatability study
 - To evaluate treatment of 1,4 dioxane in domestic water from residential wells
 - Used combination of ozone addition and ultraviolet radiation
 - Phase 1 - bench scale study of the treatment system
 - Phase 2 - pilot test of the system
 - Phase 3 – pilot scale test at the CFS landfill



1,4 Dioxane Treatability Study for Private Wells

- Results
 - Bench scale - system was effective in removing 1,4 dioxane
 - » Depending on influent concentrations, may require multiple passes through the system
 - Pilot test - 4 locations sampled, only two had detectable influent concentrations
 - » System was able to reduce the low results to non-detectable, but influent levels were much lower than anticipated.



1,4 Dioxane Treatability Study for Private Wells

- Pilot test at CFS landfill

Figure 1.0 Front view of system showing the ozone generator, carbon post-filter and system controls:




Figure 1.1 Rear view of system showing pre-filter, ozone contact tank and UV lamp chamber:





- Reduced 1,4-dioxane to ND

Public Water Supply

- 2010 - EPA took over waterline activities from NJDEP April 2010
- 2010 - 2011 - EPA conducted predesign activities
- 2011 - 2013 - Conducted design and permitting activities
- July 2013 - Commencement of waterline construction activities
- April 2015 - Waterline startup
- June 2015 - Remedial construction completion
- July 15, 2015 - Remedial action completion of waterline activities
 - Construction Cost: approximately \$9 million












Scope and Role of Action



Remedial Action Objectives

- RAOs for the OU1 ROD amendment
 - Limit migration of contaminated groundwater and leachate from OU1 to OU2
 - Enhance the treatment plant to reduce concentrations of 1,4-dioxane being discharged to surface water
 - Reduce the toxicity, mobility and volume of contamination in the North Waste Cell to reduce impact on groundwater
 - Prevent exposure to contaminated groundwater

- RAO for OU2 Interim remedy
 - Prevent current and future exposure to human receptors
 - (via ingestion, dermal contact and inhalation) to site-related contaminants in groundwater and surface water at concentrations in excess of federal and state standards

OU1 ROD Amendment and Interim OU2 ROD

OU1 ROD Amendment and Interim OU2 ROD issued September 28, 2018



- OU1-G3 Selected Remedy: Addition of new bedrock extraction wells, upgrade OU1 GWET system, source area removal, and LTM/ICs
 - Capital Cost - \$10,457,289
 - Annual O&M Cost - \$920,360
 - Present Worth Cost - \$21,933,592
 - Time Frame >30 years

- OU2-G2 Selected Remedy: Long-term monitoring/institutional controls
 - Capital Cost - \$0
 - Annual O&M Cost - \$111,200
 - Present Worth Cost - \$ 781,100
 - Time Frame - 10 years

Remedial Design Activities

- September 2018 - EPA contracted HDR to conduct RD activities
- Design changes
 - Designed for a new treatment plant facility
 - Eliminated excavation of North Waste Cell area
- Estimated Costs
 - Construction - \$23,455,533
 - O&M - \$847,777
- January 2021 - Submittal of final RD

- USACE will conduct RA activities



03

Impacts of Evolving Investigative Technologies

Evolving Technology


Cause of and solution to site problems post-cap/GWET

1. Lab methods/detections

- 1,4-Dioxane detections
- PFAS
- Changed direction of site history

2. Geophysics

- Identified nature/extent of contamination
- Extraction well network design



Evolving Technologies

- Laboratory Methods & Detection Limits
- Geophysical Methods
 - Bedrock fracture location
 - Downhole testing



Laboratory Testing

- Large technology improvement over course of project
 - Changing list of COCs
 - 1,4-Dioxane became leading COC and drove much of 2018 RI/FS and 2020 RD
 - Incorporate PFAS treatment into 2020 RD
 - Future contaminants???
- Challenges created
 - Evolving lab methods
 - Evolving toxicity data and regulatory standards



1980's




1980's

- Priority pollutant list
- COCs no longer included
 - Freon
 - Methylene chloride
 - Tert-butyl alcohol
 - Chlorobenzenes
 - Ethyl ether

2010's

- TCL/TAL
- Revised COCs
 - 1,4-Dioxane
 - Benzene
 - TCE
 - DEHP
 - Alpha-BHC
 - Lead
 - Chromium
 - TICs: phenobarbital





Normal post-remedy system operation

Water line extension
OU2 GW Investigation
2018 ROD
2020 RD
New extraction system
& treatment plant

EAST ST. WESTWOOD



1,4-Dioxane Detections

Challenge: 1,4-Dioxane's Moving Target

Media	Year	Standard or Criterion (ppb)	Citation
Groundwater	2008	10	Ground water quality standard (NJDEP), based on higher PQL
Groundwater	2010	6.1	Tap water screening level based on 1×10^{-6} excess cancer risk (EPA)
Groundwater	2010	3	Interim specific ground water criterion (NJDEP)
Groundwater	2010	0.35	Revised interim specific ground water criterion (NJDEP)
Groundwater	2014	0.67	Tap water screening level based on 1×10^{-6} excess cancer risk (EPA)
Groundwater	2015	0.4	Draft interim specific ground water criterion (NJDEP)
Groundwater	2018	0.4	Ground water quality standard (NJDEP)
Soil	2006	58/260/0.006 (ppm)	Site-specific calculated criteria (res, non-res, impact to gw) (NJDEP)
Surface Water	2003	22,000	Ecological Screening Levels (EPA Region 5)
Sediment	2003	119	Ecological Screening Levels (EPA Region 5)

PFAS – 2019/2020

- First sampling at the site in November 2019
 - Plant influent sample
- Quickly incorporated PFAS analysis into future PDI work
 - packer testing
 - pump testing
 - full round of monitoring wells in 2020
- Incorporated into design based on anticipated promulgation of standards

Analyte	NJDEP GWQS (ng/l)	EPA Health Advisory (ng/l)	Influent	Influent (Dup)	Effluent	Field Blank
			PF-INF- 20191120-0	PF-INF- 20191120-1	PF-EFF- 20191120-0	PF-FB- 20191120-0
			11/20/2019	11/20/2019	11/20/2019	11/20/2019
PFNA	13		< 4.0 UJ	< 4.0 UJ	< 4.0 UJ	< 4.0 UJ
PFOS	13		15.3 J	16.5 J	7.47 J	< 4.0 UJ
PFOA	14		28.0 J	28.9 J	29.6 J	< 4.0 UJ
Sum of PFOS and PFOA		70	43.3 J	45.4 J	37.1 J	< 4.0 UJ

Challenges Overcome & Lessons Learned


- Changing standards late in submittal cycles
- 2018 RI/FS
 - NJDEP 1,4-Dioxane GWQS promulgated at 0.4 ug/L in 2018
 - RL for RI samples 0.5 ug/L
- 2020 RD
 - NJDEP PFAS GWQS promulgated in 2020
- Keep up with evolving research on emerging contaminants including regulatory standards and proposed standards, laboratory methods and treatment options
- Work with labs to determine RLs of COCs




Geophysical Testing


- Geophysical Technologies
 - Surface geophysics
 - Electromagnetic survey to multi-stage approach
 - » Resistivity and Willowstick
 - Downhole geophysical testing improvements
 - FLUTe profiling & Multiport Wells
- Impact on site
 - Target specific fractures for further geophysical testing (horizontally and vertically)
 - Delineate bedrock contamination – MW locations
 - Design extraction well network

1980's Geophysics



2010's Geophysics






2018 RI/FS - Conceptual Site Model

Geophysics

- 1986 RI
 - Electromagnetic terrain conductivity (EM)
 - Downhole geophysics
 - Packer testing
- 2020
 - Surface geophysics staged approach
 - Resistivity
 - Willowstick Electromagnetic Survey
 - Downhole geophysics
 - FLUTe profiling
 - Packer testing








Figure E2



GEOPHYSICAL INVESTIGATION
COMBE LANDFILL SUPERFUND SITE
CHESTER, NJ
May 2019 File No. 2019019





Hager GeoScience, Inc.
596 Main Street, Woburn, MA 01801
(781) 935-8111 hgi@hagergeoscience.com



Resistivity

Surface Geophysics – Step 1




Resistivity

Location of fractures along transect/ERT lines
Direction/Dip of fractures

Willowstick


Surface Geophysics - Step 2

- Provides results over larger area
- Establish survey area based on results of resistivity
- Identify electrode placement




Willowstick Technology

- Electric current introduced to ground via 2 electrodes
- Current will flow through conductive portions of bedrock, i.e. water bearing fractures
- Magnetic field measurements on ground surface can track the flow of electric current
- Data reduced to determine fracture locations



Magnetometric Resistivity Instrument





Willowstick

Step 2

- Predicted magnetic field

vs.



- Actual magnetic field detected
- Differences indicate flow paths



Willowstick


Step 2

- Data interpretation leads to identifying fracture locations



Magnetometric Resistivity Study at Combe Fill South Landfill OU2





Surface Geophysics Results

Resistivity & Willowstick

Challenges Overcome & Lessons Learned

Geophysics

- Avoid field work in summer or after large storms
- Effects of terrain, man-made features on results
 - Power lines
 - Fences
 - Buried utilities
 - Buried waste
- Wire theft
- Works best in areas with limited development/surrounding population






Downhole Geophysics

Downhole geophysics, FLUTe hydraulic profiling and packer testing

Downhole geophysics


1986 RI


- Gamma
- Resistance
- Spontaneous potential
- Caliper
- Temperature
- Density



2018 RI


- Same as 1986 plus
- Heat-pulse flow meter
- Acoustic televiewer
- Optical televiewer





- Results and interpretations
 - Rock fabric and changes (optical televiewer)
 - Fracture dip angles/directions
 - Fracture communication
 - Borehole flow characteristics (HPFM)

NOTES:
 1.) This map was created from GPS data points collected by HGI and an aerial photo provided by Bing Maps.
 2.) The position of the aerial photo relative to surveyed HGI points is approximate.
 3.) Well locations labels indicate approximate area of well locations



Legend

CFTW-1 (Ybh) Approximate well location area (Unit symbol from Volkert 1990,2009)

Order of Rose and Polar Diagrams
 Top: All Data
 Middle: Foliation
 Bottom: Fracture Data

Plate 1	
February 27, 2020	File No. 2019019
Borehole Geophysical Survey Structure Data Combe Landfill Superfund Site Chester, NJ	
Hager GeoScience, Inc. 596 Main Street, Woburn, MA 01801 (781) 935-8111 hgi@hagergeoscience.com	

FLUTe Hydraulic Profiling

Additional downhole geophysical testing method




Water FLUTe Systems

Multiport well system allowing for depth-discrete sample intervals within same borehole



FLUTe Hydraulic Profiling

- Rate of liner installation changes when fractures are sealed by liner
- FLUTe uses data to calculate transmissivities of fractures




FLUTe Lessons Learned & Challenges

- High bedrock head pressures
 - Heavy mud or grout required for installation
 - Scaffold to overcome artesian heads for installation
- Sampling issues over time
 - Clogging ports
 - Changing head pressures
 - Leaking systems




Started From...

- Solid, foundational understanding of site geology/hydrogeology




Now we are here...

- RI/FS
 - Locate multiport monitoring wells for RI/FS
 - Extent of 1,4-Dioxane contamination





Started From...



Now we are here...


- RD
 - Design extraction network
 - Well locations & pumping rates





04

Treatment of Emerging Contaminants



Existing Groundwater Treatment System


- Treats groundwater extracted from shallow recovery wells around the landfill perimeter
- Treatment capacity design is 120 gpm, but operating at 70 gpm since start-up
- Treatment for organic (volatile and semi-volatile) and inorganic (heavy metals) contaminants
- NJDEP currently provides O&M of the treatment system and landfill

Purpose of New Design

- Increase groundwater capture from overburden and bedrock aquifers to keep contamination within the OU1 landfill property
- Add groundwater treatment for 1,4-dioxane and PFAS
- Evaluate redesign of existing treatment building vs new construction
- OU2 interim remedy is long-term monitoring




Existing Treatment Plant Process Flow Diagram



1,4-Dioxane Background

- Colorless liquid with a faint, sweet odor
- Used as a solvent stabilizer, textiles, paints, and personal care products, to name a few.
- Hydrophilic and miscible in water
- Probably human carcinogen with a one in a million (10^{-6}) risk level of $0.35 \mu\text{g/l}$.
- NJ GWQS is $0.4 \mu\text{g/l}$.




Property	1,4-dioxane
Molecular Weight	88.1
Melting Point ($^{\circ}\text{C}$ at 760 mm Hg)	11.8
Boiling Point ($^{\circ}\text{C}$ at 760 mm Hg)	101.1
Flash Point ($^{\circ}\text{C}$ at 760 mm Hg)	5 to 18
Density (g/mL at 20°C)	1.0329
Water Solubility (mg/L at 20°C)	Miscible
Vapor Density (air=1)	3.03
Octanol-Water Partition Coefficient (KOW)	0.27
Vapor Pressure (mm Hg at 20°C)	30
Henry's Law Constant (atm m ³ /mole)	4.88×10^{-6}

Source: EPA, 2006

Ex-Situ 1,4-Dioxane Treatment Technologies

- Adsorption
- Biological Treatment
- Advanced Oxidation Processes (AOP)

“I have not failed.
I've just found 10,000 ways
that won't work.”
— Thomas A. Edison



Ex-Situ 1,4-Dioxane Treatment Alternatives

- Adsorption
 - 2017 Ambersorb 563™ pilot
- Advanced Oxidation Processes (AOP)
 - 2012 NJDEP Pilot Studies
 - 2019 Fenton's Reagent bench
 - 2019 Sodium Persulfate bench
 - 2019 UV/Peroxide (3 bench)
 - 2020 UV/Peroxide pilot (Trojan UV)
- Biological Treatment (co-metabolic)
 - 2019 NJIT's DD4 and propane bench
 - 2019 DD4, PH-06, and CB1190 and propane




Adsorption

Physical adherence or bonding of ions and molecules onto the surface of another molecule.

Applications include:

- **Granular Activated Carbon (GAC)**
 - Not effective at low concentrations and short contact times; however, GAC has been demonstrated to have adsorption capacity at high concentrations and extended contact times.


- **Carbonaceous Resin – AMBERSORB 563™**
 - AMBERSORB 563™ is a synthetic resin material that is proprietary to DOW Chemical and Emerging Compounds Treatment Technologies, Inc. (ECT)



AMBERSORB 563™ Pilot Study

- ECT performed a one-month pilot study during February 2017.
 - Tested raw influent, treated effluent, and elevated 1,4-dioxane concentrations from monitoring well CF-209D.
 - Demonstrated the resin regeneration process.
- The pilot test consistently yielded effluent concentrations less than 0.4 µg/l.
- AMBERSORB 563™ showed good adsorption capacity, but was impacted by other organic compounds, resulting in the need for pre-treatment.





Source: ECT2 (<https://www.ect2.com/>)

Biological Treatment

The use of microorganisms to detoxify or remove organic or inorganic compounds from the environment.

Applications include:

▪ Metabolic

- Direct consumption
- 1,4-Dioxane metabolizers
CB1190 & PH-06


▪ Cometabolic

- Indirect consumption
- 1,4-Dioxane cometabolizer
Azoarus (DD4) (NJIT – Dr.
Mengyan Li)



Biological Treatment Phase 1 Study

- Objective: to screen and evaluate the suitability and effectiveness of various cultures and consortia to remove the target contaminants to a desirable level.
- DD4 (NJIT), PH-06 & CB1190 mix, tested in microcosm with propane and control



Contact Mengyan Li: <https://people.njit.edu/faculty/ianli>

AOP

The oxidation of organic material in water via hydroxyl radicals ($\cdot\text{OH}$)

Applications include:

- Fenton's chemistry – Hydrogen peroxide (H_2O_2) and ferrous iron (typically iron(II) sulfate (FeSO_4))
- Hydrogen peroxide (H_2O_2) and ultraviolet (UV) light
- H_2O_2 and ozone (O_3) based treatment (HiPOx)
- Photocatalytic oxidation using titanium dioxide (TiO_2) and UV light

2012 NJDEP Pilot Studies

- Purifics Photo-Cat Pilot Test 1 (May/November 2012)
 - Titanium dioxide (TiO₂)/ultraviolet (UV) light
- Kerfoot Pilot Test (Nanozox™) (August 2012)
 - Hydrogen peroxide (H₂O₂) and Ozone (O₃)
 - The Nanozox™ system uses a pulsed injection of gaseous microbubbles of ozone without leaving any detectable byproducts



Fenton's Reagent Bench Test Study


- Catalyst – Ferrous Sulfate (FeSO_4) in acidified solution (pH 2.0) with nitric acid (HNO_3)
- Oxidant – H_2O_2
- Evaluated samples from the treatment plant influent and effluent water.
 - Oxidant doses: 100 (0.01%), 500 (0.05%), and 1,000 (0.1%) mg/l.
 - Contact times: 30, 60, and 120 minutes.
- Fenton's chemistry was able to successfully destroy 1,4-dioxane to concentrations less than $0.4\mu\text{g/l}$.



Fenton's Reagent Bench Test

GWET Effluent Sample									
Oxidant Dose (mg/L)	Sample	Reaction Time (min)	Conc. (ug/L)	Sample	Reaction Time (min)	Conc. (ug/L)	Sample	Reaction Time (min)	Conc. (ug/L)
100 (low)	1	30	16.4	4	60	1.78	7	120	1.65
500 (medium)	2		0.2 U	5		0.2 U	8		0.1 U
1,000 (high)	3		0.2 U	6		0.1 U	9		0.2 U
Control			25.2						

Monthly H₂O₂ Cost vs Flow Rate




Hydrogen Peroxide and UV

- Low Pressure vs Medium Pressure lamps
- UVT at various stages within the treatment train
- Peroxide dose and other design factors
- Multiple technology vendors:
 - Atlantium Technologies, Ltd. – Performed collimated beam, low pressure bench test (2019)
 - Calgon UV – Performed medium-pressure bench test (2019)
 - Trojan UV – Performed preliminary evaluation (2019) and low-pressure lamp field pilot test in 2020




Atlantium Bench Test




Calgon UV Bench Test

Bench Test - Run 1 & 2



Trojan UV Pilot Test

- 1-Month pilot test using a low-pressure UV lamps.
- Tested water from post-lamella clarifier, post sand-filters, and during a system-wide pump test.
- Varied UV lamp intensity, peroxide dosage from 10 mg/l to 400 mg/l, and flow rate from 5 to 10 gpm.




Trojan UV Pilot Test Results

Run Location	Flow Rate, gpm	Peroxide Dose, mg/l	Lamp Intensity	Sample ID	Field Parameters				Lab Results	
					UVT	Temp, °C	pH	Turbidity, NTU	1,4-dioxane	% Reduction
Post-Lamella Clarifier	5	10	100	CF-LC-IN-10-100-20200317-0	61.7	13.88	8.15	37.2	18	-
	5	10	100	CF-LC-EF-10-100-20200317-0	65.4	14.14	8.11	35.1	1.7	91%
	5	20	100	CF-LC-IN-20-100-20200317-0	60.5	13.93	8.41	37.2	19	-
	5	20	100	CF-LC-EF-20-100-20200317-0	65.3	14.08	8.24	35.6	0.59	97%
	5	30	100	CF-LC-IN-30-100-20200317-0	60.8	14.16	8.06	39.8	19	-
	5	30	100	CF-LC-EF-30-100-20200317-0	63.9	13.81	7.92	37.5	0.18	99%
	5	40	100	CF-LC-IN-40-100-20200317-0	57.5	12.72	8.86	36.8	19	-
	5	40	100	CF-LC-EF-40-100-20200317-0	63	13.72	8.59	39.4	0.19	99%
Post-Sand Filter	5	10	100	CF-SF-IN-10-100-5-20200324-0	84.8	12.25	8.39	6.16	36	-
	5	10	100	CF-SF-EF-10-100-5-20200324-0	91.5	12.47	7.26	5.75	0.25	99%
	10	20	100	CF-SF-IN-20-100-10-20200324-0	84.5	10.34	7.84	7.41	31	-
	10	20	100	CF-SF-EF-20-100-10-20200324-0	90.3	11.33	7.65	8.36	0.23	99%
	10	50	100	CF-SF-IN-50-100-10-20200324-0	85	13.94	8.08	6.56	34	-
	10	50	100	CF-SF-EF-50-100-10-20200324-0	89.4	12.35	7.55	6.22	0.079	100%

Technology Comparison

Technology	Pros	Cons
Adsorption technology using regenerable resin.	<ul style="list-style-type: none"> Consistently achieved treatment goal. Easy to operate/ regenerable in place. Does not require use of chemicals for treatment. 	<ul style="list-style-type: none"> Produces waste stream requiring disposal. Proprietary technology.
AOP via Fenton's Reagent	<ul style="list-style-type: none"> Able to achieve treatment goal. Non-proprietary technology. 	<ul style="list-style-type: none"> Requires large volumes of chemicals for treatment.
AOP treatment using UV and H ₂ O ₂	<ul style="list-style-type: none"> Reliably met treatment goals. Multiple competing technology vendors. Small footprint and easily scalable. 	<ul style="list-style-type: none"> Higher electric usage. Chemical storage required. UV bulb replacement
Bioaugmentation of Propanotrophs (NJIT - DD4 bacteria species)	<ul style="list-style-type: none"> Sustainable, green remediation. Low carbon footprint depending on food source used. 	<ul style="list-style-type: none"> Sensitive to environmental factors. DD4 is unproven at full scale application and requires further R&D.



Proposed Groundwater Treatment System


Proposed Design


- Design flowrate of 450 gpm from 22 groundwater extraction wells (overburden and bedrock aquifers) around the landfill
- Optimized treatment system to remove 1,4-dioxane and PFAS from extracted groundwater using UV/peroxide and GAC
- New construction adjacent to the existing building/ exterior tanks
- Reuse and retrofitting of some existing infrastructure



Engineering Design Tools

- LiDAR 3D scan of existing facility
- Autodesk Suite
 - Navisworks/ ReCap
 - Revit/ CAD
 - BIM 360







Proposed New Treatment Plant Location

Aerial Imagery (2012), NJDEP NJ-GeoWeb, Service Layer Credits


Proposed Extraction System



Proposed Treatment Plant Process Flow Diagram



Metals Removal Sand Filtration UV Light/Peroxide Activated Carbon



GROUND FLOOR PLAN
3/10" = 1'-0"



Lessons Learned/ Takeaways

- Read
- Go to the Site
 - Take pictures and notes
- Ask Questions
 - Technical vendors can teach you
- **TALK TO THE OPERATOR!!**






So... What has changed over time?

- The COCs (time passing, natural degradation, emerging contaminants previously unknown, improvements in laboratory detection limits)
- The treatability technologies (vast improvements in relatively short period of time)
- The groundwater containment strategy
 - Number, locations, and pumping rates of extraction wells (deep vs. shallow)
- Higher resolution investigative technologies (improvements in downhole instruments, new inventions such as FLUTe and Willowstick)



What has stayed the same?

- Conceptual Site Model (CSM)
- Tried and true hydrogeologic methods – e.g., pump tests, potentiometric surface maps from water levels
- Lengthy process of investigation and design
- Stakeholders add to complexity
- This is only the beginning of THE FINISH!



Questions?