




# Chlorinated Solvent DNAPL Extent Characterization



East Gate Disposal Yard  
Fort Lewis  
Washington



## Presentation Purpose

- Discuss Triad investigation approach.
- Explain NAPL characterization tools used at EGDY.
- Discuss CSM of EGDY DNAPL.

2

# TCE in Groundwater



3



## EGDY History

- Received Logistics Center wastes from 1946 – 1970's.
- Cleaning and degreasing solvents and POLs.
- Disposed in trenches in drums, free liquid or burned.



## EGDY Characterization Methods

- Dynamic investigation approach.
- Systematic planning.
- Real time data collection.
- Qualified field personnel.


5

## Investigation Chronology

- Two phases due to funding constraints.
- Phase I: 1998 – 1999.
- EE/CA.
- Drum Removal Action.
- Phase II: 2001 – 2002.

# Phase I DQOs

- Evaluate if significant NAPL present beneath EGDY to provide continuing source of TCE to groundwater.
- Estimate extent of LNAPL and DNAPL if present.
- Refine hydrogeologic understanding.



## Phase I Toolbox


- Aerial photography.
- EM-61.
- Soil gas sampling.
- Exploratory trenches.
- Drive point groundwater sampling.
- On site GC analysis.




8




# Aerial Photo Analysis Results



9




# EM-61 Survey Results



10



# Soil Gas Sampling



11




# Exploratory Trenching



12



# Exploratory Trenching Results




## Direct Push Drive Point Groundwater Sampling




14

# Drive Point Groundwater Results



15



## EE/CA

- Purpose: to evaluate remedial alternatives to accelerate cleanup and reduce overall costs.
- Preferred alternative:
  - Optimize P&T system.
  - Remove source area drums.
  - Thermal treatment of NAPL contaminated source soils and groundwater.

16




# Drum Removal



17

# Drum Removal Results



18



## Phase II DQOs

- Obtain data for NAPL thermal treatment design.
- Obtain data for P&T optimization.
- Obtain data for reactive barrier wall options.
- Provide analytical results to segregate and classify IDW.
- Field generated data turn-around time supports real-time decision making needs.



19

## Phase II Toolbox

- SCAPS LIF.
- Geoprobe MIP.
- Resistivity and GPR.
- Sonic Coring.
  - UV fluorescence.
  - Sheen tests.
  - Hydrophobic dye tests.
  - PID.
- Soil physical analyses.
- Multi-port wells.




20

# Geoprobe MIP



21

# MIP Results



22




# Sonic Drilling




23

# Sonic Drilling Results







# NW – SE Cross Section



# Selection of Treatment Volumes



26



## TCE Mass Estimate

	TCE	
Description	Mass (lbs)	Volume (gal)
Drum Removal	50,000	4,000
Remaining NAPL	100,000	10,000
Dissolved Plume	10,000	1,000

27

## TPH Mass Estimate

Description	TPH	
	Mass (lbs)	Volume (gal)
Drum Removal	100,000	20,000
Remaining NAPL	600,000	80,000
Dissolved Plume	--	--

28

## Conclusions

- Triad investigation method:
  - Insured adequate data for thermal design.
  - Reduced investigation time.
- Contract for thermal remediation awarded September 2002.
- Thermal treatment to begin late 2003.